

MODEL 7 1/2'



Digging depth.....	7.5'
Reach of swing pivot.....	114.1"
Loading height (bucket at 60°)	57.0"
Swing arc.....	180°
Transport height (maximum).....	72.4"
Tractor horsepower.....	20-40
Bucket rotation	160°
Stabilizer spread, down position	84.25"
Stabilizer spread, up position	60.6"
Shipping weight (less bucket).....	1,057 lbs.
Bucket digging force	3,100 lbs.
Dipperstick digging force	2,231 lbs.
Operating pressure.....	2100 PSI
Gear increaser ratio	3.35:1
Maximum pressure.....	3680 lbs./in ²
Operating pressure.....	2650 lbs./in ²
Gallons per minute....	3-5 GPM depending on PTO RPM's

ALL HYDRAULIC HOSES ARE MADE WITH US THREADS

MODEL 10 1/2'

MORE POWER...STRENGTH & DURABILITY



\$12,000.00 VALUE for \$6,445.00
with choice of one bucket • 18", 24", 36" buckets available
Pump & Reservoir \$600.00 with backhoe purchase
Pump & Reservoir \$795.00 without backhoe purchase
 18" bucket - \$365.00 • 24" bucket - \$435.00 • 36" bucket - \$495.00

\$7,000.00 VALUE for \$4,295.00

with choice of one bucket • 8", 12", 18" buckets available
Pump & Reservoir \$600.00 with backhoe purchase
Pump & Reservoir \$795.00 without backhoe purchase
 8" bucket - \$300.00 • 12" bucket - \$325.00 • 18" bucket - \$350.00

<http://www.rustictractors.com/backhoe.htm>

Digging depth.....	10.5'
Reach of swing pivot.....	145.5"
Loading height (bucket at 60°)	75.8"
Swing arc.....	180°
Transport height (maximum).....	95.0"
Tractor horsepower.....	50 + IF equipped with front loader
.....	OR 65 + w/o front loader
Stabilizer spread, down position	130.7"
Stabilizer spread, up position	91"
Shipping weight (less bucket).....	1,891 lbs.
Bucket digging force	6,100 lbs.
Dipperstick digging force	3,200 lbs.
Operating pressure.....	2320 PSI
Maximum RPM.....	3000
Gear increaser ratio	3.00:1.00
Maximum pressure.....	3527 PSI
Gallons per minute.	3.5 - 5 GPM depending on PTO RPM's

ALL HYDRAULIC HOSES ARE MADE WITH US THREADS

Prices subject to change without notice®